

CNG Dispenser

Advantages

- Hi-tech but economical
- 3rd party inspection of dispensers
- Accurate and quick dispensing
- LCD digital prominent display
- Efficient technical support
- Factory calibrated
- Extra long hose (Optional)
- Stainless steel tubing & fittings
- Ease of maintenance by optimum layout of mechanical, electrical and electronics components
- Micro processor controlled

Specification

Rated working pressure	Max. Inlet Pressure: 25 Mpa=250bar
	Max. Outlet Pressure: 20 Mpa=200bar
Power supply	Single Phase AC, 220 V+/-10%, 50Hz
Solonoid valve control voltage	220 AC
Display	
Total Amount	6 Digits 1" high
Total Quantity	6 Digits 1" high
Unit Amount	4 Digits 1/2" high
Electro Mechanical Totalizer	6 Digits
Maximum Service Pressure	P max. 25 Mpa=250 bar
Minimum Service Pressure	P max. 07 Mpa=70 bar
Meter Accuracy	+/-1%
Length of Hose	4m
Flow rate	1-15-38.6kg/min (max)
Test Pressure	300 bar
Ambient Temperature Range	- 40 C to + 55 C
CNG Temperature Range	- 40°C to + 75°C
Air Humidity	10% - 95% R ^o H

Most Suitable for Buses & Trucks